- 1. A method for determining the quality of a result of a clustering data processing operation, the result comprising a set of clusters, a cluster having a set of buckets for each variable, the method comprising the steps of:
 - a) determining a foreground frequency of a bucket within a first cluster;

in is

The state of the s

(1) |1115

- b) determining a background frequency of the bucket with respect to all of the clusters;
- c) comparing the foreground and background frequencies; and
- d) determining a quality index based on the comparison.

'l] 20

- 2. The method of Claim 1, wherein said comparing step further comprises subtracting the relative foreground and background frequencies.
- 3. The method of Claim 2, wherein said comprising step further comprises squaring the result of the comparison.
 - 4. The method of Claim 1, further comprising the steps of:
 - e) determining an optimal number of clusters; and

- 5 The method of Claim 4, wherein the optimal number of clusters is determined by a maximum number of buckets for a variable.
- 10 The method of Claim 5, wherein the optimal number of clusters is set to a threshold value in case the maximum number es b 15 of buckets is greater than the threshold value.
 - The method of Claim 4, further comprising the steps of: 7.

[] in in

20

25

- g) determining a factor based on the optimal number of clusters and the actual number of clusters; and
- h) multiplying the result of the comparison of the relative foreground and background frequencies with the factor.
- The method of Claim 7, further comprising the steps of:
 - i) determining a normalizing value being independent of any correlations between fields of the data on which the data processing operation is applied; and

ξπb

The second secon

jest kat

- j) normalizing the result of the comparison of the foreground and background frequencies by means of the normalizing value.
- 5 9. The method of Claim 8, wherein said step of determining the normalizing value further comprises:
 - i) comparing the background frequencies of the buckets with an imaginary cluster having a foreground frequency of the bucket equal to one;
 - ii) comparing the background frequencies of the buckets with an imaginary cluster having a foreground frequency of the bucket equal to zero; and
 - iii) summing the results of the corresponding comparison values.
 - 10. A method for data clustering, said method comprising the steps of:
 - a) performing a number of data clustering operations;
- b) determining a quality index for each result of the data clustering operations; and
 - c) selecting the result with the highest quality index as an end result of the data clustering.



- 11. A method for data clustering, said method comprising the steps of:
 - a) selecting an initial set of clusters;

- b) determining a quality index for the clusters; and
- c) performing a number of iterations to improve the quality index.

10

ash

The state of the s

in in

20

25

- 12. The method of Claim 11, further comprising the steps of:
 - d) moving at least one record of at least one of the clusters to another cluster;

e) determining the quality index for the modified clusters; and

f) using the modified clusters as a new initial set of clusters in case the quality index improved.

13. A computer program product stored on a computer usable medium for determining the quality of a result of a clustering data processing operation, the result comprising a set of clusters, a cluster having a set of buckets for each variable, the method comprising the said program product comprising:

determining first subprocesses for a foreground frequency of a bucket within a first cluster;

IJ





determining second subprocesses for a background frequency of the bucket with respect to all of the clusters;

5 comparing third subprocesses the foreground and background frequencies; and

determining fourth subprocesses a quality index based on the comparison.